TE Internal #: AEA577N0000201000 17 Position Circular Connector, Cable-to-Panel, Signal, Panel Mount, Electrodeposited Nickel, Zinc Alloy, PBT GF, 17 Signal Positions, 23 Shell Size

#### View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors



Number of Positions: 17

Connector System: Cable-to-Panel

Sealable: No

Circuit Application: Signal

Connector Mounting Type: Panel Mount

### Features

### Product Type Features

Connector Product Type	Connector Assembly
Connector System	Cable-to-Panel
Sealable	No
Circular Connector Type	Receptacle
Shell Type	Metal
Configuration Features	
Number of Positions	17
Number of Signal Positions	17
Electrical Characteristics	
Operating Voltage	125 VDC
Body Features	
Environmental Protection	IP67
Shell Plating Material	Electrodeposited Nickel
Shell Base Material	Zinc Alloy

**C** For support call+1 800 522 6752

17 Position Circular Connector, Cable-to-Panel, Signal, Panel Mount, Electrodeposited Nickel, Zinc Alloy, PBT GF, 17 Signal Positions, 23 Shell Size



Circular Connector Insulation Material Type	PBT GF
Mechanical Attachment	
Panel Mount Feature Type	Flange with Mounting Holes
Mating Retention Type	Screw
Connector Mounting Type	Panel Mount
Housing Features	
Circular Connector Shell Size	23
Alignment Keyed	0°
Usage Conditions	
Operating Temperature Range	-20 – 130 °C[-4 – 266 °F]
Operation/Application	
Durability Rating	500 Cycles
Circuit Application	Signal
Shielded	Yes
Industry Standards	
UL Flammability Rating	UL 94V-0
Compatible With Approved Standards Products	UL

### Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these

17 Position Circular Connector, Cable-to-Panel, Signal, Panel Mount, Electrodeposited Nickel, Zinc Alloy, PBT GF, 17 Signal Positions, 23 Shell Size



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Customers Also Bought**





Documents

**CAD** Files

3D PDF

3D

Customer View Model ENG\_CVM\_CVM\_AEA577N00000201000\_A.2d\_dxf.zip English Customer View Model ENG\_CVM\_CVM\_AEA577N00000201000\_A.3d\_igs.zip English Customer View Model ENG\_CVM\_CVM\_AEA577N00000201000\_A.3d\_stp.zip English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages AEA577N00000201000

English

fuer Datenblaetter, die online konfigurierbar sind

**C** For support call+1 800 522 6752

17 Position Circular Connector, Cable-to-Panel, Signal, Panel Mount, Electrodeposited Nickel, Zinc Alloy, PBT GF, 17 Signal Positions, 23 Shell Size



German