# DT16-18SC-K004 ~ ACTIVE

#### DEUTSCH | DEUTSCH DT

TE Internal #: DT16-18SC-K004

18 Position Housing, Housing for Female Terminals, Wire-to-Wire,

4.67 mm [.184 in] Centerline, Sealable, Black, Wire & Cable, Power,

DEUTSCH DT

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings











Number of Positions: 18

Connector & Housing Type: Housing for Female Terminals

Mating Pin Diameter: 1.59 mm [ .063 in ]

Connector System: Wire-to-Wire
Centerline (Pitch): 4.67 mm [.184 in]

#### **Features**

#### **Product Type Features**

| Mixed & Hybrid Connector          | No                           |
|-----------------------------------|------------------------------|
| Connector Shape                   | Rectangular                  |
| Connector & Housing Type          | Housing for Female Terminals |
| Connector System                  | Wire-to-Wire                 |
| Sealable                          | Yes                          |
| Primary Locking Feature           | Integrated in Housing        |
| Connector & Contact Terminates To | Wire & Cable                 |

## **Configuration Features**

| Connector Modification | Enhanced Seal Retention, End Cap |
|------------------------|----------------------------------|
| Number of Positions    | 18                               |
| Number of Rows         | 3                                |

#### **Electrical Characteristics**

| Operating Voltage            | 250 VDC          |
|------------------------------|------------------|
| Nominal Voltage Architecture | 12 V, 24 V, 48 V |



## **Body Features**

| Cable Exit Angle        | 180°  |
|-------------------------|-------|
| Primary Product Color   | Black |
| Connector & Keying Code | С     |

## **Contact Features**

| Contact Size                 | Size 16          |
|------------------------------|------------------|
| Contact Type                 | Socket           |
| Mating Pin Diameter          | 1.59 mm[.063 in] |
| Contact Current Rating (Max) | 13 A             |

#### Mechanical Attachment

| Strain Relief               | With                       |
|-----------------------------|----------------------------|
| Terminal Position Assurance | No                         |
| Mating Alignment Type       | Keyed                      |
| Mating Alignment            | With                       |
| Connector Mounting Type     | Cable Mount (Free-Hanging) |

## **Housing Features**

| Housing Material   | PA GF            |
|--------------------|------------------|
| Centerline (Pitch) | 4.67 mm[.184 in] |

#### **Dimensions**

| Row-to-Row Spacing                   | 4.83 mm[.19 in]               |
|--------------------------------------|-------------------------------|
| Compatible Insulation Diameter Range | 1.35 – 3.05 mm[.053 – .12 in] |
| Product Width                        | 20.98 mm[.826 in]             |
| Product Length                       | 35.38 mm[1.393 in]            |
| Connector Height                     | 43.82 mm[1.725 in]            |

## **Usage Conditions**

| Operating Temperature (Max) | 125 °C[257 °F]             |
|-----------------------------|----------------------------|
| Operating Temperature Range | -55 – 125 °C[-67 – 257 °F] |

## Operation/Application

| Circuit Application | Power |
|---------------------|-------|
| Industry Standards  |       |

#### Industry Standards

| IP Rating              | Not Tested |
|------------------------|------------|
| UL Flammability Rating | Not Tested |



#### **Packaging Features**

| Packaging Quantity | 500 |
|--------------------|-----|
| Packaging Method   | Box |

#### Other

| Serviceable                          | Yes |  |
|--------------------------------------|-----|--|
| Connector Position Assurance Capable | No  |  |

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant  |
|---|--|
| EU ELV Directive 2000/53/EC                   | Compliant  |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold  |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2025 (247)  Candidate List Declared Against: JAN 2025 (247)  SVHC > Threshold:  Dodecamethylcyclohexasiloxane (D6) (.5% in 27519632271)  Decamethylcyclopentasiloxane (D5) (.5% in 27519632271)  Octamethylcyclotetrasiloxane (D4) (.5% in Component Part)  Article Safe Usage Statements:  Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.   |
| Solder Process Capability                     | Not reviewed for solder process capability   |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



## Compatible Parts
















## Also in the Series | DEUTSCH DT



Automotive Connector Locks & Position Assurance(92)



Automotive Housings(736)



Connector Caps & Covers(1)




Connector Seals & Cavity Plugs(18)



Connector Strain Relief(31)



Other Automotive Connector Accessories(28)



PCB Headers & Receptacles(107)



Rectangular Backshells & Clamps(3)



Wire-to-Board Headers & Receptacles (106)




## Customers Also Bought



TE Part #HC5899
BAT CONNECTOR POS8MM
AUXILLARY MNT



TE Part #K1136510 Relay 31-311-11-i



TE Part #HC5738

95MM2 POSBAT LEAD 1/4" UNC
THREAD















### **Documents**

**Product Drawings** 

PLG, 18P, BLK, E, C

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_DT16-18SC-K004\_G.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DT16-18SC-K004\_G.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DT16-18SC-K004\_G.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

18 Position Housing, Housing for Female Terminals, Wire-to-Wire, 4.67 mm [.184 in] Centerline, Sealable, Black, Wire & Cable, Power, DEUTSCH DT



Datasheets & Catalog Pages
TERMINALS AND CONNECTORS

English

**Product Specifications** 

**Application Specification** 

English