

DTM04-2P-EP10

✓ ACTIVE

DEUTSCH | DEUTSCH DT, DEUTSCH DTM

TE Internal #: DTM04-2P-EP10

2 Position Housing, Housing for Male Terminals, Component-to-Wire, 4.19 mm [.165 in] Centerline, Sealable, Black, Wire & Cable, Power, Hybrid

[View on TE.com >](#)



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH DTM Housings



Number of Positions: 2

Connector & Housing Type: **Housing for Male Terminals**

Mating Pin Diameter: 1.02 mm [.04 in]

Connector System: **Component-to-Wire**

Centerline (Pitch): 4.19 mm [.165 in]

[All DEUTSCH DTM Housings \(113\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Male Terminals
Connector System	Component-to-Wire
Sealable	Yes
Primary Locking Feature	Integrated in Housing
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Blank Cavity Position	0
Connector Modification	Terminating Resistor, J1939
Number of Positions	2
Number of Rows	1



Electrical Characteristics

Operating Voltage	250 VDC
Nominal Voltage Architecture	12 V, 24 V, 48 V

Body Features

Cable Exit Angle	180°
Primary Product Color	Black
Connector & Keying Code	B

Contact Features

Contact Size	Size 20
Contact Type	Pin
Mating Pin Diameter	1.02 mm[.04 in]
Contact Current Rating (Max)	7.5 A

Mechanical Attachment

Strain Relief	Add By Accessory
Terminal Position Assurance	Yes
Mating Alignment Type	Keyed
Mating Alignment	With

Housing Features

Housing Material	PA GF
Centerline (Pitch)	4.19 mm[.165 in]

Dimensions

Compatible Insulation Diameter Range	1.35 – 3.05 mm[.053 – .12 in]
Product Width	16.54 mm[.651 in]
Product Length	42.67 mm[1.68 in]
Connector Height	16.21 mm[.638 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

IP Rating	IP68, IP6K9K
-----------	--------------



Compatible With Agency/Standards Products	SAE J2030
UL Flammability Rating	20mm Flame Test per Standard UL-94

Packaging Features

Packaging Quantity	1000
Packaging Method	Box

Other

Serviceable	No
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Dodecamethylcyclohexasiloxane (D6) (.5% in 27519632267) Decamethylcyclopentasiloxane (D5) (.5% in 27519632267) Pb (1.2% in 74005426) Octamethylcyclotetrasiloxane (D4) (.5% in 27519632267) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on




requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts




TE Part # 1924487-2
MOUNTING CLIP, AMPSEAL 16




TE Part # DT-RT1
EXT TOOL, FRONT RELEASE




TE Part # 1060-20-0244
PIN, SF, SIZE 20, 16-22, AU/SN




TE Part # CAT-D48-ST273
DEUTSCH Solid Contacts




TE Part # 1060-20-0122
PIN, SF, SIZE 20, 16-22, NI/NI




TE Part # CAT-D485-CH8172
DEUTSCH DTM Housings




TE Part # 1060-20-0222
PIN, SF, SIZE 20, 16-22, NI/NI



TE Part # 1060-20-0144
PIN, SF, SIZE 20, 16-22, AU/SN




TE Part # 1028-021-0205
BKSHL, 2P, BLK, REC, ST, NW 7.5/8.5




TE Part # CAT-D487-M8649
DEUTSCH DT Mounting Clips


Also in the Series | DEUTSCH DT




Automotive Connector Caps & Covers
(7)




Connector Caps & Covers(1)



Rectangular Connector Housings(1)



Rectangular Power Connectors(77)




Standard Rectangular Connectors(1)

Also in the Series | **DEUTSCH DTM**



Automotive Connector Caps & Covers (7)




Automotive Connector Locks & Position Assurance(26)




Automotive Housings(109)



Connector Strain Relief(28)



Other Automotive Connector Accessories(7)



PCB Headers & Receptacles(38)

Customers Also Bought



TE Part #CAT-AQ4-PHA1400
PowerTube HVP-HD 1400 Accessories and Plug Components



TE Part #53124-1
TERMINAL,SOLIS SPR SPD 16-14 8



TE Part #DT16-6SA-KP01
PLG, 6P, GRY, E, A



TE Part #53127-1
TERMINAL,SOLIS SPR SPD 12-10 8




TE Part #DTM06-2S
PLG, 2P, GRY, N



TE Part #2387549-4
CU ALLOY,INNER FERRULE,150SQ



TE Part #ASA046N0007050A000
617 PLUG, SPEEDTEC



TE Part #2-2399608-1
3POS,HVP1400,ASSY,180DEG,COD A /B/C



Documents

Product Drawings

REC, 2P, BLK, 120 OHM RESISTOR, AU, B

English

CAD Files

Customer View Model

ENG_CVM_CVM_DTM04-2P-EP10_99.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_DTM04-2P-EP10_99.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DTM04-2P-EP10_99.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

TERMINALS AND CONNECTORS

English

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English