DTM13-12PA-R008 ✓ ACTIVE

DEUTSCH | DEUTSCH DT, DEUTSCH DTM

TE Internal #: DTM13-12PA-R008

PCB Mount Header, Right Angle, Wire-to-Board, 12 Position, 4.19 mm [.165 in] Centerline, Fully Shrouded, Nickel (Ni), Through Hole -

Solder, Hybrid

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > DEUTSCH DTM Headers











PCB Connector Type: PCB Mount Header

PCB Mount Orientation: Right Angle
Connector System: Wire-to-Board

Number of Positions: 12

Number of Rows: 2

All DEUTSCH DTM Headers (37)

Features

Product Type Features

Mixed & Hybrid Header	No
Connector Shape	Rectangular
PCB Connector Type	PCB Mount Header
Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Connector Product Type	Connector Assembly

Configuration Features

Connector Modification	PCB Enclosure Header
Number of Signal Positions	12
Number of Sections	1
PCB Mount Orientation	Right Angle



Number of Positions	12
Number of Rows	2
Electrical Characteristics	
Operating Voltage	250 VDC
Voltage Rating (Max)	250 VDC
Nominal Voltage Architecture	12 V, 24 V
Body Features	
Connector & Keying Code	A
Primary Product Color	Black
Contact Features	
Mating Pin Diameter	1.02 mm[.04 in]
Contact Size	Size 20
Contact Mating Area Plating Material	Nickel (Ni)
Contact Type	Pin
Contact Current Rating (Max)	7.5 A
Termination Features	
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Panel Mount Feature	Without
Mating Retention Type	Locking Interface
Mounting Holes	With
Mating Retention	With
PCB Mount Retention Type	Mounting Screw
Mating Alignment Type	Keyed
PCB Mount Retention	With
PCB Mount Alignment	Without
Connector Mounting Type	Panel Mount
Mating Alignment	With
Housing Features	
Centerline (Pitch)	4.19 mm[.165 in]
Dimensions	
Connector Width	60.96 mm[2.4 in]



PCB Thickness (Recommended)	.78 – 1.57 mm[.031 – .062 in]
Connector Length	36.91 mm[1.453 in]
Profile Height from PCB	25.71 mm[1.012 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Shielded	No
Circuit Application	Signal
Industry Standards	
IP Rating	IP67, IP6K9K
UL Flammability Rating	Not Tested
Packaging Features	
Packaging Quantity	105
Packaging Method	Box
Other	

Product Compliance

Interface Number

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

DTM04-12P

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as



EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts












Also in the Series | DEUTSCH DT












Also in the Series | DEUTSCH DTM





Automotive Connector Caps & Covers



Automotive Connector Locks & Position Assurance(26)




Automotive Housings(109)



Connector Strain Relief(28)



Other Automotive Connector Accessories(7)



PCB Headers & Receptacles(38)

Customers Also Bought



TE Part #1-644753-2 12P MTA156 HDR ASSY RN STR F/L



RP 1E 0.1W 255K 0.1% 25PPM 1K RL



DTM13-12PA-R019, HDR,12P, BLK,RA, NI/CU,A





TE Part #9-146458-0 40 MODII HDR SRST UNSHRD STKG



TE Part #1877285-7 07P EP SHRD HDR ASMY, WHITE



ENCLOSURE, 3.25 X 4, BLK, VENT





TE Part #7001003-ZZ RESISTOR ASSMB PL

Documents



Product Drawings

HDR, 12P, BLK, RA EEC, NI/CU, A

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_DTM13-12PA-R008_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_DTM13-12PA-R008_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DTM13-12PA-R008_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

English