

DEUTSCH | DEUTSCH DT, DEUTSCH DTP

TE Internal #: DTP04-2P

2 Position Housing, Housing for Male Terminals, Wire-to-Wire, 6.71 mm [.264 in] Centerline, Sealable, Gray, Wire & Cable, Power,

Hybrid

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH DTP Housings











Number of Positions: 2

Connector & Housing Type: Housing for Male Terminals

Mating Pin Diameter: 2.4 mm [.094 in]

Connector System: Wire-to-Wire
Centerline (Pitch): 6.71 mm [.264 in]

All DEUTSCH DTP Housings (34)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Male Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Primary Locking Feature	Integrated in Housing
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Blank Cavity Position	0
Connector Seal Code	N Seal
Number of Positions	2

Number of Rows



Electrical Characteristics

Operating Voltage	200 VDC
Nominal Voltage Architecture	12 V, 24 V

Body Features

Cable Exit Angle	180°
Primary Product Color	Gray

Contact Features

Contact Size	Size 12
Contact Type	Pin
Mating Pin Diameter	2.4 mm[.094 in]
Contact Current Rating (Max)	25 A

Mechanical Attachment

Strain Relief	Without
Terminal Position Assurance	No
Mating Alignment Type	Polarization
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PA GF
Centerline (Pitch)	6.71 mm[.264 in]

Dimensions

Compatible Insulation Diameter Range	3.4 – 4.3 mm[.134 – .169 in]
Product Width	22.1 mm[.87 in]
Product Length	22.1 mm[.87 in]
Connector Height	47.3 mm[1.86 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application

Circuit Application	Power
Industry Standards	

IP68, IP6K9K

IP Rating



Compatible With Agency/Standards Products	SAE J2030
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	1
Packaging Method	Package
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Dodecamethylcyclohexasiloxane (D6) (.5% in Component Part) Decamethylcyclopentasiloxane (D5) (.5% in Component Part) Octamethylcyclotetrasiloxane (D4) (.5% in 27520761152) Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



TE Part # CAT-D486-CH8172 DEUTSCH DTP Housings



TE Part # 1060-12-0166 PIN, SF, SIZE 12, 12-14, NI/SN







TE Part # 1060-12-0222 PIN, SF, SIZE 12, 10, NI/NI



TE Part # WP-2P WEDGE LOCK, 2P, REC, ORG, DTP





















Also in the Series | DEUTSCH DT





Automotive Connector Caps & Covers (19)



Connector Caps & Covers(1)




Rectangular Connector Housings(1)



Rectangular Power Connectors(5)



Also in the Series | DEUTSCH DTP



Automotive Connector Locks & Position Assurance(4)



Automotive Headers(5)



Automotive Housings(34)




Connector Seals & Cavity Plugs(2)



Insertion & Extraction Tools(3)



Other Automotive Connector Accessories(4)



PCB Headers & Receptacles(5)



Rectangular Backshells & Clamps(3)



Wire-to-Board Headers & Receptacles (5)



Customers Also Bought













Documents

Product Drawings

REC, 2P, GRY, N

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_DTP04-2P_99_c-dtp04-2p-99.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_DTP04-2P_99_c-dtp04-2p-99.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DTP04-2P_99_c-dtp04-2p-99.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

TERMINALS AND CONNECTORS

English

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

2 Position Housing, Housing for Male Terminals, Wire-to-Wire, 6.71 mm [.264 in] Centerline, Sealable, Gray, Wire & Cable, Power, Hybrid



Product Specifications

Engineering Report

English

Engineering Report

English

Agency Approvals

UL Report

English