



HX-CT

TE Internal #: EL8211-000

Continuous, Low Fire Hazard, 2:1, Yellow, 38.1 mm [1.5 in]
Expanded Inside, Shrinks To 19 mm [.75 in], HX-CT, Printable
Tubing

[View on TE.com >](#)

Identification & Labeling > Printable Tubing > Continuous Tube, Low Fire Hazard HX-CT



Printable Tubing Type: **Continuous**
Printable Tubing Grade: **Low Fire Hazard**
Shrink Ratio: **2:1**
Primary Product Color: **Yellow**
Expanded Inside Diameter (Min): **38.1 mm [1.5 in]**

[All Continuous Tube, Low Fire Hazard HX-CT \(50\)](#)

Features

Product Type Features

Printable Tubing Type	Continuous
Printable Tubing Grade	Low Fire Hazard

Body Features

Shrink Ratio	2:1
Primary Product Color	Yellow

Dimensions

Expanded Inside Diameter (Min)	38.1 mm[1.5 in]
Recovered Inside Diameter (Max)	19 mm[.75 in]
Compatible Cable Diameter Range	19 – 30.48 mm[.75 – 1.2 in]

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Printer/Label Features

Printer Technology	Thermal Transfer
--------------------	------------------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)




EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1-2186501-1
T3212-SWARE-PRINTER



TE Part # 1-2186500-1
T3212-PRINTER



TE Part # 1-2186502-1
T3224-PRINTER



TE Part # 1-2186503-1
T3224-SWARE-PRINTER



TE Part # EC9926-000
PRINTER-UNIVERSAL-REEL-HOLDER



Also in the Series | [HX-CT](#)



[Printable Tubing\(50\)](#)

Customers Also Bought



TE Part #EC7637-000

[HLX104YW1TS050B](#)



TE Part #CAT-T3437-H99

[HX-SCE Low Fire Hazard Sleeves](#)



TE Part #176819-000

[B-150-11](#)



TE Part #270225-000

[B-150-07](#)




TE Part #CAT-T3437-W919

[WP White Polyester Labels](#)



TE Part #031307-000

[B-150-13](#)



TE Part #5068004001

[CGPT-38/19-9-SP](#)

Documents

Product Drawings

[HX-CT-40M-38.1-OUT-4](#)

English

Datasheets & Catalog Pages

[Printable Continuous Tubing](#)

English

[HX-CT, Low Fire Hazard Continuous Heat Shrink Identification Tube](#)

English

[Cable Identification Product Shelf Life](#)

English

Product Specifications

[Product Specification](#)

English

EL8211-000

Continuous, Low Fire Hazard, 2:1, Yellow, 38.1 mm [1.5 in] Expanded Inside, Shrinks To 19 mm [.75 in], HX-CT, Printable Tubing



Instruction Sheets

Instruction Sheet (non U.S.)

English