## Split Banding Ring

TE Internal #: EM6347-000

Split Ring Ferrule, Composite, Split Banding Ring

View on TE.com >



Connectors > Connector Accessories > Connector Strain Relief



Strain Relief Accessory Type: Split Ring Ferrule

Primary Product Material: Composite

Operating Temperature Range: -65 – 175 °C [-85 – 347 °F]

## **Features**

## **Product Type Features**

| Strain Relief Accessory Type                | Split Ring Ferrule         |
|---|----------------------------|
| Body Features                               |                            |
| Primary Product Material                    | Composite                  |
| Dimensions                                  |                            |
| Product Length                              | 22.35 mm[.88 in]           |
| Usage Conditions                            |                            |
| Operating Temperature Range                 | -65 – 175 °C[-85 – 347 °F] |
| Industry Standards                          |                            |
| Compatible With Approved Standards Products | 85049/93                   |
| Other                                       |                            |
| Entry Size Code                             | 14                         |

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Not Yet Reviewed  |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2025<br>(247)<br>Candidate List Declared Against: JUNE<br>2022 (224) |



|            |         | REACH  | CV/II/C    |
|------------|---------|--------|------------|
| $n \cap T$ | CONTAIN | RFA( H | $\sim VH($ |
|            |         |        |            |

|  | w Halogen - Br, Cl, F, I < 900 ppm per<br>mogenous material. Also BFR/CFR/PVC<br>ee |
|--|---|
|--|---|


Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Also in the Series | Split Banding Ring



# **Customers Also Bought**























## **Documents**

**Product Drawings** 

R85049/93-14

English

Datasheets & Catalog Pages

Circular Backshells

English