

HDP26-24-9SE-L017

✓ ACTIVE

DEUTSCH | [DEUTSCH HDP](#), [DEUTSCH HD](#)

TE Internal #: HDP26-24-9SE-L017

9 Position Housing, Housing for Female Terminals, Wire-to-Panel, Sealable, Black, Wire & Cable, Power, Panel Mount, Hybrid

[View on TE.com](#) >



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH HDP20 Housings



Number of Positions: 9

Connector & Housing Type: **Housing for Female Terminals**

Mating Pin Diameter: 2.4 mm, 3.6 mm, 5.7 mm [.094 in, .142 in, .225 in]

Connector System: **Wire-to-Panel**

Sealable: **Yes**

[All DEUTSCH HDP20 Housings \(357\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	Yes
Connector Shape	Circular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Panel
Sealable	Yes
Primary Locking Feature	Contact Retainer
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Blank Cavity Position	0
Connector Modification	Ring Adapter
Connector Seal Code	E Seal
Number of Positions	9

Electrical Characteristics

Operating Voltage	250 VDC
Nominal Voltage Architecture	12 V, 24 V, 48 V

Body Features

--	--



Cable Exit Angle	180°
------------------	------

Primary Product Color	Black
-----------------------	-------

Contact Features

Contact Size	Size 12, Size 4, Size 8
--------------	-------------------------

Contact Type	Socket
--------------	--------

Mating Pin Diameter	2.4 mm, 3.6 mm, 5.7 mm[.094 in][.142 in][.225 in]
---------------------	---

Contact Current Rating (Max)	25 A, 60 A, 100 A
------------------------------	-------------------

Mechanical Attachment

Strain Relief	Without
---------------	---------

Terminal Position Assurance	No
-----------------------------	----

Mating Alignment Type	Polarizing Slot
-----------------------	-----------------

Mating Alignment	With
------------------	------

Connector Mounting Type	Panel Mount
-------------------------	-------------

Housing Features

Housing Material	PA 66 GF
------------------	----------

Dimensions

Compatible Insulation Diameter Range	3.6 – 5.2 mm[.14 – .204 in]
--------------------------------------	-----------------------------

Product Width	49.5 mm[1.95 in]
---------------	------------------

Product Length	49.5 mm[1.95 in]
----------------	------------------

Connector Height	42.5 mm[1.67 in]
------------------	------------------

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
-----------------------------	----------------

Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

IP Rating	IP67
-----------	------

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	40
--------------------	----

Packaging Method	Tray
------------------	------



Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Dodecamethylcyclohexasiloxane (D6) (.5% in 27520273107) Decamethylcyclopentasiloxane (D5) (.5% in 27520273107) Octamethylcyclotetrasiloxane (D4) (.5% in 27520273107) Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # HD30-24BT-90-BK
BOOT, 24SZ, RA, BLK



TE Part # HD30-24BT
BOOT, 24SZ, ST, GRY



TE Part # CAT-D48-SP729
DEUTSCH Sealing Plugs



TE Part # CAT-H396-CH8172
DEUTSCH HDP20 Housings



TE Part # CAT-H396-B128
DEUTSCH HDP20 Backshells



TE Part # 0411-204-1605
EXT TOOL, SIZE 16, 16-18 AWG, N, DRK BLU



TE Part # 0411-337-1205
EXT TOOL, SIZE 12, 12-14 AWG, E, ORG



TE Part # 114008-ZZ
EXT TOOL, SIZE 8, 8-10 AWG, N, GRN



TE Part # 114009-ZZ
EXT TOOL, SIZE 4, 6 AWG, N, WHT



TE Part # HD30-24BT-BK
BOOT, 24SZ, ST, BLK

Also in the Series | **DEUTSCH HD**




Automotive Connector Caps & Covers
(4)



Automotive Housings(357)



Other Automotive Connector
Accessories(6)



PCB Headers & Receptacles(1)



Rectangular Power Connectors(1)

Also in the Series | **DEUTSCH HDP**



Automotive Connector Caps & Covers (4)



Automotive Housings(357)



Connector Seals & Cavity Plugs(1)



Other Automotive Connector Accessories(6)

Customers Also Bought



TE Part #2292863-3
AS16,CAP BACKSHELL KIT,ST,06P, NC12



TE Part #DT06-08SC-CE05
PLG, 8P, GRN, E, SEAL RET, CAP, C




TE Part #52948
PG SP SPD 22-16COMM22-18MIL 5



TE Part #2098252-3
PIN, SF, SIZE 16, 14-16 AWG, NI/SN



TE Part #CAT-H396-CH8172
DEUTSCH HDP20 Housings



TE Part #16-04477AD
GASKET HD30/HDP20 24 SHL ADHESIVE BACK

Documents

Product Drawings

PLG, 9P, BLK, E, RNG, 4/8/12, S

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_HDP26-24-9SE-L017_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_HDP26-24-9SE-L017_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_HDP26-24-9SE-L017_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.



Datasheets & Catalog Pages

DEUTSCH HD30 & HDP20 CONNECTOR SERIES

English

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English