

## KISSLING | KISSLING Series 29

TE Internal #: K1060611

General Purpose Power Relay, DC, Monostable, 1 Form X SPST-NO-

DM, 300 A Contact Rating, 18 VDC / 32 VDC Coil Voltage,

KISSLING Series 29

View on TE.com >



Relays & Contactors > Electromechanical Relays > Power Relay, 300A, Standard, Monostable, DC



Relay & Contactor Type: General Purpose Power Relay

Current Type: DC

Coil Magnetic System: Monostable

Contact Arrangement: 1 Form X SPST-NO-DM

Contact Current Rating: 300 A

All Power Relay, 300A, Standard, Monostable, DC (22)

## **Features**

#### **Product Type Features**

Froduct Type Features	
Relay & Contactor Type	General Purpose Power Relay
Configuration Features	
Coil Special Features	Coil Suppression Diode
Contact Number of Poles	1
Contact Arrangement	1 Form X SPST-NO-DM
Electrical Characteristics	
Coil Resistance	62 Ω
Contact Current Rating	300 A
Coil Voltage Rating	18 VDC, 32 VDC
Contact Voltage Rating	28 VDC
Coil Power Rating DC	10 W
Contact Features	
Contact Material	Silver Alloy
Mechanical Attachment	

Mounting Brackets

Product Mounting Feature Type



Product Mount Type	Chassis Mount

#### **Dimensions**

Product Width	62 mm[2.44 in]
Product Length	120 mm[4.72 in]
Product Height	55.5 mm[2.18 in]

# Operation/Application

Current Type	DC
Coil Magnetic System	Monostable

#### **Packaging Features**

Packaging Method	Carton	
------------------	--------	--

#### Other

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Pb (93.2% in 17071202736) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





TE Part # CAT-AL6-KSPR29300 Power Relay, 300A, Standard, Monostable, DC



TE Part # CAT-AL6-KSPR30300 Power Relay, 300A, Standard, Bistable, 2 Coils, Polarized



TE Part # K1023465 Relay 29-314-12-903

# Also in the Series | KISSLING Series 29





Electromechanical Relays(123)

# Customers Also Bought





















TE Part #K1060319 Relay 29-211-12A



W57-XB1A7A10-10=CKTBKR,THERM,

PB,SCW/QC

## **Documents**

# **Product Drawings**

Relay 29-311-12A

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_29-311-12A\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_29-311-12A\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_29-311-12A\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

# Datasheets & Catalog Pages

KISSLING SINGLE POLE POWER RELAYS Series 29 / 300A

English