



Switches > Battery Disconnect Switches > Battery Disconnect, 400A, 1 Pole



Switch Main Contact Current Rating: 400 A

Operating Voltage: 32 VDC

Number of Poles: 1

Operating Handle Type: Pointer Key Handle

Termination Thread Size: M10

[All Battery Disconnect, 400A, 1 Pole \(22\)](#)

Features

Product Type Features

Sealed Device	Yes
---------------	-----

Configuration Features

Number of Poles	1
Number of Auxiliary Contacts	0
Switch Keying Option	Not Removable

Electrical Characteristics

Operating Voltage	32 VDC
Switch Main Contact Current Rating	400 A

Body Features

Operating Handle Color	Red
------------------------	-----

Mechanical Attachment

Operating Handle Type	Pointer Key Handle
Termination Thread Size	M10
Switch Mounting Option	Long Flange

Dimensions

Screw Hole Diameter	6.5 mm[.256 in]
---------------------	-----------------



Centerline Between Flange Screw Holes

100 mm[3.937 in]

Usage Conditions

Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]
-----------------------------	---------------------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Pb (2.5% in 4748716719) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts






Also in the Series

KISSLING Series 35




Battery Disconnect Switches(175)



Rotary Switches(6)


Customers Also Bought




TE Part #EK4824-000
91H1-09-04-1-B-HE050




TE Part #CAT-EMIG-0008
Std MIL-DTL-38999 Series Conn Gasket




TE Part #2423911-1
Conn G SNG 38999 S2 Shell 11 & 12




TE Part #1-1393315-1
V23132B2002B200=HCR




TE Part #CAT-J41-DDRC
DEUTSCH DT Receptacle Connectors



TE Part #DT06-4S
PLG, 4P, GRY, N



TE Part #K1144876
Limit switch G12-212-M-10



TE Part #W4P
WEDGE LOCK, 4P, REC, GRN, DT

Documents

Product Drawings

Battery Disconnecter 35-411-151-R

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_35-411-151-R_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_35-411-151-R_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_35-411-151-R_A.3d_stp.zip



English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

KISSLING BATTERY DISCONNECTOR Series 35 / 400A

English