

### KISSLING | KISSLING Series DS

TE Internal #: K1145355

1 Position, Short Handle Selector, 1 Decks, Red Actuator, Selector,

2 Switch, Thermoplastic, Sealed, KISSLING Series DS, Rotary

Switches

View on TE.com >



Switches > Rotary Switches > Rotary Switch, Center Thread, Short Handle Selector, Sealed



Number of Positions: 1

Actuator Style: Short Handle Selector

Number of Decks: 1
Actuator Color: Red

Rotary Switch Type: Selector

All Rotary Switch, Center Thread, Short Handle Selector, Sealed (12)

### **Features**

#### **Product Type Features**

Product Type Features	
Switch Connection Type	DIN Connector
Actuator Style	Short Handle Selector
Rotary Switch Type	Selector
Sealed Device	Yes
Configuration Features	
Number of Positions	1
Number of Decks	1
Number of Switches	2
Operating Function	Change Over 2 Pole, Maintained
Electrical Characteristics	
Contact Current Rating	5 A
Operating Voltage	32 VDC
Body Features	
body i editires	

Thermoplastic

Vertical

Case Material

**Product Orientation** 



#### **Mechanical Attachment**

## **Product Compliance**


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Pb (3% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



Also in the Series | KISSLING Series DS





## Customers Also Bought











TE Part #1546307-2 2P .374" DR BARRIER,W/WASHER



Push button switch TS-221-GE11









## **Documents**

Product Drawings
Rotary Switch DS-221-RT1

English

Rotary Switch DS-221-RT1

German

**CAD Files** 

3D PDF

3D

1 Position, Short Handle Selector, 1 Decks, Red Actuator, Selector, 2 Switch, Thermoplastic, Sealed, KISSLING Series DS, Rotary Switches



**Customer View Model** 

ENG\_CVM\_CVM\_DS-221-RT1\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DS-221-RT1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DS-221-RT1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

KISSLING ROTARY SWITCH Series DS

English