# CONSMA013.031-G V ACTIVE

TE Internal #: L9000274-01

SMA Connector, Plug, 50 ohm, Threaded, 0 – 18 GHz, 1 Position, Printed Circuit Board, Board Mount, -65 – 165 °C [-85 – 329 °F],

Solder, Straight

View on TE.com >



#### Connectors > RF Connectors > Coax Connectors



RF Interface: SMA

RF Connector Style: Plug

Impedance:  $50 \Omega$ 

RF Connector Coupling Mechanism: Threaded

Operating Frequency: 0 – 18 GHz

#### **Features**

### **Product Type Features**

Connector Product Type	Connector Assembly
RF Interface	SMA
RF Connector Style	Plug
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

## **Configuration Features**

PCB Mount Orientation	Edge
Number of Positions	1
Number of Coaxial Contacts	1

# **Electrical Characteristics**

lman a dan aa	50 Ω
Impedance	30.75

### **Body Features**

Cable Connector Orientation	Straight
Body Material	Brass
Body Material Finish	Plated
Body Plating Material	Gold

#### **Contact Features**

RF Connector Center Contact Plating Material	Gold (Au)
--	-----------



RF Connector Center Contact Material	Brass
Termination Features	
Termination Method to Wire & Cable	Solder
Mechanical Attachment	
RF Connector Coupling Mechanism	Threaded
Connector Mounting Type	Board Mount
RF Contact Captivation Method	Mechanical
Detent	Without
Usage Conditions	
Operating Temperature Range	-65 – 165 °C[-85 – 329 °F]
Operation/Application	
Circuit Application	Signal
Operating Frequency	0 – 18 GHz
Packaging Features	
Packaging Quantity	100
Packaging Method	Tray
Other	
Dielectric Material	PTFE

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

# Compatible Parts



TE Part # CONSMA011-R178 SMA Jack 50 Ohm Cable Crimp



TE Part # CONSMA012 SMA RA Plug 50 Ohm Cable Crimp



TE Part # CONSMA002-SMD-G-T SMA Jack 50 Ohm PCB Surface Mount



TE Part # CONSMA018-15-G SMA Jack 50 Ohm Panel Mount



TE Part # L9000269-01 SMA Jack 50 Ohm .062 PCB Edge Mount



TE Part # CONSMA002 SMA RA Jack 50 Ohm PCB Through Hole



TE Part # CONSMA005 SMA Jack 50 Ohm Cable Crimp



TE Part # CONSMA011 SMA Jack 50 Ohm Cable Crimp



TE Part # CONSMA024-G-T SMA Jack 50 Ohm PCB Edge Mount



TE Part # L9000277-01 SMA Jack 50 Ohm .031 PCB Edge Mount



SMA Jack 50 Ohm Panel Mount



TE Part # CONSMA024-G SMA Jack 50 Ohm PCB Edge Mount





TE Part # CONSMA011-R58

SMA Jack 50 Ohm Cable Crimp



TE Part # CONSMA017

SMA Jack 50 Ohm Panel Mount



TE Part # CONSMA014-R178-G SMA Jack 50 Ohm Cable Crimp Panel Mount

SMA Connector, Plug, 50 ohm, Threaded, 0 – 18 GHz, 1 Position, Printed Circuit Board, Board Mount, -65 – 165 °C [-85 – 329 °F], Solder, Straight





TE Part # L9000272-01 SMA Jack 50 Ohm .062 PCB Edge Mount



TE Part # L9000280-01 SMA Jack 50 Ohm .062 PCB Edge Mount




TE Part # CONSMA002-G SMA Jack 50 Ohm PCB Through Hole



# Customers Also Bought



TE Part #L9000276-01 SMA Plug 50 Ohm .062 PCB Edge Mount



TE Part #102308-000 2020D0309-0



TE Part #6-1879131-9 RN 0402 10K 0.1% 10PPM 5K RL



TE Part #5-794630-2 22P MICRO MNL ASSY,VRT,HDR,LF



TE Part #L9000277-01 SMA Jack 50 Ohm .031 PCB Edge Mount



TE Part #925590-2 MINI SPRING RECEPTACLE



TE Part #4-1879233-1 SMW5 4R7 5%



TE Part #CONSMA002-G SMA Jack 50 Ohm PCB Through Hole



SMA Jack 50 Ohm .031 PCB Edge Mount



# **Documents**

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_L9000274-01\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_L9000274-01\_A.3d\_stp.zip

English

SMA Connector, Plug, 50 ohm, Threaded, 0 – 18 GHz, 1 Position, Printed Circuit Board, Board Mount, -65 – 165 °C [-85 – 329 °F], Solder, Straight



**Customer View Model** 

ENG\_CVM\_CVM\_L9000274-01\_A.2d\_dxf.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

SMA MALE EDGE MOUNT FOR 0.031INCH BOARD

English