## HTAT-24/6-0-SP ✓ ACTIVE

#### RAYCHEM | RAYCHEM HTAT

TE Internal #: NB07744001

Heat Shrink Tubing, Black, 4:1, Dual Wall, Shrinks To 6 mm [.236 in], Irradiated Modified Polyolefin, 24 mm [.945 in] Expanded Inside,

RAYCHEM HTAT

View on TE.com >



Heat Shrink Tubing > HTAT Heat Shrink Tubing











Tubing Product Type: Heat Shrink Tubing

Primary Product Color: Black

Shrink Ratio: 4:1
Wall Type: Dual Wall

Recovered Inside Diameter (Max): 6 mm [ .236 in ]

All HTAT Heat Shrink Tubing (66)

### **Features**

### **Product Type Features**

Tubing Product Type	Heat Shrink Tubing
Wall Type	Dual Wall

#### **Electrical Characteristics**

Operating Voltage (Max)	.6 kV	
-------------------------	-------	--

#### **Body Features**

Fluid Type	Diesel Fuel, Hydraulic Fluid, Lubricating Oil, Motor Oil, Water
Primary Product Color	Black
Shrink Ratio	4:1
Primary Product Material	Irradiated Modified Polyolefin
Flexibility	Semi-Flexible

#### **Dimensions**



Recovered Wall Thickness (Nominal)	2.25 mm[.088 in]
Recovered Wall Thickness (Tolerance)	.55 mm[.022 in]
Recovered Inside Diameter (Max)	6 mm[.236 in]
Expanded Inside Diameter (Min)	24 mm[.945 in]
Tubing Size Range	6 – 24 mm[.236 – .945 in]

### **Usage Conditions**

Resistance Properties	Moisture
Shrink Temperature (Min)	80 °C
Tubing Flammability Type	Flame-Retardant
Operating Temperature Range	-55 – 125 °C
Recovery Temperature	110 °C

### Operation/Application

Mechanical Resistance Fluids, M	Mechanical Damage, Strain Relief
---------------------------------	----------------------------------

### **Product Availability**

### Packaging Features

Packaging Method Reel
-----------------------

#### Other

Meets Low Outgassing Requirements	No
Product Source	Czech Republic

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability




#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


## **Compatible Parts**



## Also in the Series | RAYCHEM HTAT



# **Customers Also Bought**

















### **Documents**

Product Drawings HTAT-24/6-0-SP

English

Datasheets & Catalog Pages HTAT Pages from 9-1773447-9

English

Product Specifications

Application Specification

English