1899849-2 ACTIVE

RAYCHEM | RAYCHEM ATUM

TE Internal #: NB11354001

Heat Shrink Tubing, Black, 4:1, Dual Wall, Shrinks To 13 mm [.512 in], Irradiated Modified Polyolefin, 52 mm [2.047 in] Expanded Inside, RAYCHEM ATUM

View on TE.com >



Heat Shrink Tubing > ATUM 4:1 Heat Shrink Tubing



Tubing Product Type: Heat Shrink Tubing

Primary Product Color: Black

Shrink Ratio: 4:1
Wall Type: Dual Wall

Recovered Inside Diameter (Max): 13 mm [.512 in]

All ATUM 4:1 Heat Shrink Tubing (85)

Features

Product Type Features

Tubing Product Type	Heat Shrink Tubing
Wall Type	Dual Wall
Electrical Characteristics	
Operating Voltage (Max)	.6 kV
Body Features	
Fluid Type	Aviation Fuel, Chemicals/Solvents, De-Icing Fluid, Diesel Fuel, Hydraulic Fluid, Lubricating Oil
Primary Product Color	Black
Shrink Ratio	4:1
Primary Product Material	Irradiated Modified Polyolefin
Flexibility	Semi-Flexible



Recovered Wall Thickness (Nominal)	2.54 mm[.1 in]
Recovered Wall Thickness (Tolerance)	.55 mm[.022 in]
Recovered Inside Diameter (Max)	13 mm[.512 in]
Expanded Inside Diameter (Min)	52 mm[2.047 in]
Tubing Size Range	13 – 52 mm[.51 – 2.04 in]
Usage Conditions	

Shrink Temperature (Min)	80 °C
Tubing Flammability Type	Flame-Retardant
Operating Temperature Range	-55 – 110 °C
Recovery Temperature	110 °C

Operation/Application

Mechanical Resistance	Fluids, Mechanical Damage
-----------------------	---------------------------

Product Availability

Applicable Region	Global	

Packaging Features

Packaging Method	Reel	
------------------	------	--

Other

Meets Low Outgassing Requirements	No
Product Source	Czech Republic

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: DBMC (5% in 23647975030) Article Safe Usage Statements: Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.



Solder Process Capability

Not applicable for solder process capability


Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts



Also in the Series | RAYCHEM ATUM







Customers Also Bought






















Documents

Product Drawings
ATUM-52/13-0-SP

English

Datasheets & Catalog Pages
ATUM Tubing

English

Product Specifications

Application Specification

English