RAYCHEM | RAYCHEM RNF-150

TE Internal #: NB15734001

Heat Shrink Tubing, Black, 2:1, Single Wall, Shrinks To 1.6 mm [.062

in], Crosslinked Fluoropolymer, RAYCHEM RNF-150

View on TE.com >



Heat Shrink Tubing > RNF-150 Heat Shrink Tubing



Tubing Product Type: Heat Shrink Tubing

Primary Product Color: Black

Shrink Ratio: 2:1

Wall Type: Single Wall

Recovered Inside Diameter (Max): 1.6 mm [.062 in]

All RNF-150 Heat Shrink Tubing (27)

Features

Product Type Features

Tubing Product Type	Heat Shrink Tubing
Wall Type	Single Wall
Electrical Characteristics	
Operating Voltage (Max)	.6 kV
Body Features	

Fluid Type	Aviation Fuel, Hydraulic Fluid, Lubricating Oil, Water
Primary Product Color	Black
Shrink Ratio	2:1
Primary Product Material	Crosslinked Fluoropolymer
Flexibility	Flexible

Dimensions

Recovered Wall Thickness (Nominal)	.25 mm[.01 in]
Recovered Wall Thickness (Tolerance)	.1 mm[.004 in]
Recovered Inside Diameter (Max)	1.6 mm[.062 in]
Expanded Inside Diameter (Min)	3.18 mm[.125 in]

Usage Conditions



Shrink Temperature (Min)	110 °C
Tubing Flammability Type	Highly Flame-Retardant
Operating Temperature Range	-55 – 150 °C
Recovery Temperature	150 °C
Operation/Application	
Mechanical Resistance	Abrasion, Fluids, Mechanical Damage, Strain Relief
Product Availability	
Applicable Region	Global
Packaging Features	
Packaging Method	Spool
Other	
Meets Low Outgassing Requirements	No

Czech Republic

Product Compliance

Product Source

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits




as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | RAYCHEM RNF-150



Customers Also Bought
















Documents

Heat Shrink Tubing, Black, 2:1, Single Wall, Shrinks To 1.6 mm [.062 in], Crosslinked Fluoropolymer, RAYCHEM RNF-150



Product Drawings

RNF-150-1/8-0-SP

English

Datasheets & Catalog Pages

RNF-150 Pages from 9-1773447-9

English

Product Specifications

Application Specification

English