



TE Internal #: T2031001040-000  
Pin Contact, Silver (Ag), Locking Spring Contact Retention, 12  
AWG, Crimp, Copper Alloy, Power & Signal, -40 – 125 °C [-40 – 257  
°F]  
[View on TE.com >](#)

Connectors > Contacts > Connector Contacts > BPSC Stacked Hybrid Connector: Male Female Contact, 7-12 AWG



Contact Type: **Pin**  
Contact Mating Area Plating Material: **Silver (Ag)**  
Wire Contact Termination Area Plating Material: **Silver**  
Contact Retention Type Within Housing: **Locking Spring**  
Wire Size: **12 AWG**

[All BPSC Stacked Hybrid Connector: Male Female Contact, 7-12 AWG \(6\)](#)

Features

Product Type Features

Discrete Wire Type	Stranded
--------------------	----------

Electrical Characteristics

Contact Resistance	5 mΩ
--------------------	------

Contact Features

Contact Underplating Material	Copper or Nickel
Contact Shape & Form	Round
Contact Length	23.3 mm
Barrel Type	Closed
Contact Diameter	4.5 mm
Contact Type	Pin
Contact Mating Area Plating Material	Silver (Ag)
Wire Contact Termination Area Plating Material	Silver
Contact Base Material	Copper Alloy



Contact Current Rating (Max)	20 A
------------------------------	------

Termination Features

Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable

Mechanical Attachment

Contact Retention Type Within Housing	Locking Spring
---------------------------------------	----------------

Dimensions

Wire Size	12 AWG
-----------	--------

Usage Conditions

Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Packaging Features

Packaging Method	Bag & Box
------------------	-----------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous



materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE’s information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) ‘Guidance on requirements for substances in articles’(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of ‘complex object’, the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA “Guidance on requirements for substances in articles” (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



TE Part # T2220002040-001  
[SCEF2.5-4.0](#)



TE Part # T2100182101-000  
[BPSC-12/2/4-M](#)



TE Part # T2220002040-000  
[SCEF2.5-4.0](#)



TE Part # T2100182201-000  
[BPSC-12/2/4-F](#)


Customers Also Bought



TE Part #4-1625868-7  
[RP 2A 0.25W 16R2 0.1% 25PPM 1K RL](#)



TE Part #T2100182101-000  
[BPSC-12/2/4-M](#)




TE Part #T0931000408-000  
[M4 STAINLESS STEEL SCREW,FLAT HEAD](#)



TE Part #T2030001040-000  
[CEM-4.0](#)



TE Part #CAT-LS0-BMFC  
[BPSC Stacked Hybrid Connector: Male Female Contact, 7-12 AWG](#)



TE Part #T2100182201-000  
[BPSC-12/2/4-F](#)

Documents

Product Drawings  
[MCEM-4.0](#)

English

CAD Files  
[3D PDF](#)  
3D  
Customer View Model



[ENG\\_CVM\\_CVM\\_T2031001040-000\\_A.2d\\_dxf.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_T2031001040-000\\_A.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_T2031001040-000\\_A.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[Bess Stacked Hybrid Connector](#)

[Bess Stacked Hybrid Connector](#)

English

Product Specifications

[Application Specification](#)

English