

DTS20F17-06PN [V001] ✓ ACTIVE

DEUTSCH | DEUTSCH 38999 Series III, DEUTSCH 38999

TE Internal #: YDTS20F17-06PNV001

6 Position Circular Connector, Cable-to-Panel, Sealable, Wire & Cable, Power, Panel Mount, Electroless Nickel, DEUTSCH 38999 Series III

[View on TE.com >](#)



Connectors > Circular Connectors > Standard Circular Connectors > D38999: Square Flange, 17-06 insert



Number of Positions: 6

Connector System: **Cable-to-Panel**

Sealable: **Yes**

Connector & Contact Terminates To: **Wire & Cable**

Contact Current Rating (Max): **23 A**

[All D38999: Square Flange, 17-06 insert \(43\)](#)

Features

Product Type Features

Connector Product Type	Connector Assembly
Assembly Type	Electrical Connector
Connector System	Cable-to-Panel
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Circular Connector Type	Receptacle
Shell Type	Square Flange Receptacle

Configuration Features

Keying & Polarized Position Locations	N
Factory Installed Backshell	No
Number of Positions	6
Number of Power Positions	6
Number of Signal Positions	0
Contacts Preloaded	No

Electrical Characteristics

Operating Voltage	850 VDC
-------------------	---------



Body Features

Product Weight	25.6 g[.904 oz]
O-Ring Material	Silicone
Entry Style	Rear Insertion
Environmental Protection	Yes
Environmental Protection Type	Elastomer Sealed
Peripheral Seal Material	Silicone
Fluid Type	Coolanol 25, M2-V, MIL-DTL-5624 (JP-4,JP-5), MIL-DTL-83133 (JP-8), MIL-PRF-23699, MIL-PRF-5606, MIL-PRF-7808, SEA-AMS1424 Type I
Feedthrough Type	No
Shell Plating Material	Electroless Nickel
Shell Base Material	Aluminum 6061-T6
Circular Connector Insulation Material Type	Hard Dielectric/Silicone
Hermetically Sealed	No

Contact Features

Contact Quantity (Size 12)	6
Contact Current Rating (Max)	23 A
Reverse Gender	No
Contact Layout Arrangement	17 – 6
Circular Connector Contact Type	Pin

Mechanical Attachment

Panel Mount Feature	With
Mating Retention Type	Triple Start Threaded
Panel Mount Feature Type	Square Flange
Connector Mounting Type	Panel Mount
Polarization Code	N
Mating Alignment Type	Keyed
Mating Retention	With

Housing Features

Circular Connector Shell Size	17
Alignment Keyed	Clocking

Dimensions



Compatible Insulation Diameter Range	2.46 – 3.61 mm[.097 – .142 in]
Assembly Length	31.5 mm[1.24 in]
Wire Size	14 – 12 AWG

Usage Conditions

Operating Temperature Range	-65 – 200 °C[-85 – 392 °F]
-----------------------------	----------------------------

Operation/Application

Durability Rating	500 Cycles
Circuit Application	Power
Shielded	Yes

Packaging Features

Packaging Quantity	1
--------------------	---

Other

Position Locations Omitted	All
----------------------------	-----

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Pb (1.2% in Contact Lead-Copper Alloy) Decamethylcyclopentasiloxane (D5) (5% in Insert Assembly) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products



will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # CAT-D38999-DTS18V
Straight Plug: D38999, 17-06 Insert,
Electroless Nickel Plating

Also in the Series | DEUTSCH 38999 Series III

Standard Circular Connectors(2555)


Also in the Series | DEUTSCH 38999

Standard Circular Connectors(2555)


Customers Also Bought



TE Part #YDTS32F17NV0010000
DUST COVER ASSEM



TE Part #8-1617760-6
FCB-405-0625M=M83536/6-025M




TE Part #YCTJ122E01CC015000
ELEC MODULE



TE Part #2-1618403-6
CAP120ASANG=CONTACTOR, SPST-NO




TE Part #1662-213-2031
CONT SOC ASSY




TE Part #YCTJ-3A-10C0160000
RAIL ASSY




TE Part #YDTS20F13-98SNV001
RECP ASSY



TE Part #YCTD160E01FC015000
MODULE ASSY



TE Part #EP6584-000
S01-05-R-CS4531



TE Part #YCTJ122E10AC015000
ELEC MODULE

Documents

Product Drawings

RECP ASSY

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_YDTS20F17-06PNV001_99.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_YDTS20F17-06PNV001_99.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_YDTS20F17-06PNV001_99.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



DEUTSCH MIL-DTL-38999 Connectors Quick Reference Guide

English