HDP24-24-19PE-L024 ✓ ACTIVE

DEUTSCH | DEUTSCH HD, DEUTSCH HDP

TE Internal #: YHDP24-24-19PEL024

19 Position Housing, Housing for Male Terminals, Wire-to-Wire,

Sealable, Black, Wire & Cable, Power, Cable Mount (Free-Hanging),

Hybrid

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH HDP20 Housings











Number of Positions: 19

Connector & Housing Type: Housing for Male Terminals

Mating Pin Diameter: 1.59 mm, 2.39 mm [.063 in, .094 in]

Connector System: Wire-to-Wire

Sealable: Yes

All DEUTSCH HDP20 Housings (357)

Features

Product Type Features

Connector Seal Code

Number of Positions

Mixed & Hybrid Connector	Yes
Connector Shape	Circular
Connector & Housing Type	Housing for Male Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Primary Locking Feature	Integrated in Housing
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Blank Cavity Position	0
Connector Modification	Wide Threaded Adapter

E Seal

19



Electrical Characteristics	
Operating Voltage	250 VDC
Nominal Voltage Architecture	12 V, 24 V, 48 V
Body Features	
Cable Exit Angle	180°
Primary Product Color	Black
Contact Features	
Contact Size	Size 12, Size 16
Contact Type	Pin
Mating Pin Diameter	1.59 mm, 2.39 mm[.063 in][.094 in]

Mechanical Attachment

Contact Current Rating (Max)

Strain Relief	Add By Accessory
Terminal Position Assurance	No
Mating Alignment Type	Guide Post
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

13 A, 25 A

Housing Features

Housing Material	PA GF	

Dimensions

Compatible Insulation Diameter Range	1.35 – 3.05 mm, 2.46 – 4.01 mm[.097 – .158 in][.053 – .12 in]
Product Width	50.8 mm[2 in]
Product Length	41.53 mm[1.635 in]
Connector Height	47.63 mm[1.875 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application

Circuit Application	Power	

Industry Standards

IP Rating	IP67



UL Flammability Rating	20mm Flame Test per Standard UL-94
Packaging Features	
Packaging Quantity	1
Packaging Method	Box
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Dodecamethylcyclohexasiloxane (D6) (.5% in 27520056304) Decamethylcyclopentasiloxane (D5) (.5% in 27520056304) Octamethylcyclotetrasiloxane (D4) (.5% in 27520056304) Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



Compatible Parts



TE Part # 1060-12-0222 PIN, SF, SIZE 12, 10, NI/NI



TE Part # 16-04477 GASKET, 24SZ, BLK, HD30



TE Part # 24-D-PUNCH D-HOLE PUNCH, SIZE 24



TE Part # HD30-24BT-BK BOOT, 24SZ, ST, BLK




TE Part # CAT-H396-RC8382 Receptacle Protective Caps — DEUTSCH HDP20



TE Part # CAT-J67-DSCC16 **DEUTSCH Size 16 Crimp Contacts**



TE Part # 1060-12-0166 PIN, SF, SIZE 12, 12-14, NI/SN



TE Part # CAT-D48-ST273 **DEUTSCH Solid Contacts**



TE Part # HD30-24BT-90-BK BOOT, 24SZ, RA, BLK



TE Part # HD30-24BT BOOT, 24SZ, ST, GRY



TE Part # 62036-40 62036 HDP24 FLANGE-SEAL silicone 60shore



TE Part # CAT-D48-SFT273 DEUTSCH Stamped and Formed Contacts



TE Part # 1060-12-0144 PIN, SF, SIZE 12, 12-14, AU/SN



TE Part # 2300908-1 0460-003-16329, PIN, SOLID, 20-24AWG, AU



TE Part # CAT-D48-SP729 **DEUTSCH Sealing Plugs**





TE Part # CAT-H396-CH8172 DEUTSCH HDP20 Housings





Also in the Series | DEUTSCH HD

ORG






Automotive Connector Caps & Covers (4)



Automotive Housings(357)



Other Automotive Connector Accessories(6)



PCB Headers & Receptacles(1)



Also in the Series | DEUTSCH HDP



Automotive Connector Caps & Covers (4)



Automotive Housings(357)




Connector Backshells(10)



Connector Seals & Cavity Plugs(1)



Insertion & Extraction Tools(11)



Customers Also Bought















Documents

Product Drawings

REC, 19P, BLK, E, WTHD, 12/16, P

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_YHDP24-24-19PEL024_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_YHDP24-24-19PEL024_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_YHDP24-24-19PEL024_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

English

19 Position Housing, Housing for Male Terminals, Wire-to-Wire, Sealable, Black, Wire & Cable, Power, Cable Mount (Free-Hanging), Hybrid



Agency Approvals

UL Report

English