YHV280-2PM-P-4MM-B ACTIVE

HIVONEX

TE Internal #: YHV280-2PM-P-4MM-B

4 Position Housing, Plug, Cable-to-Cable / Wire-to-Wire, 10.4 mm [. 409 in] Centerline, Sealable, Orange, Wire & Cable, Power & Signal

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings



Number of Positions: 4

Connector & Housing Type: Plug

Mating Tab Width: .63 mm, 2.8 mm [.024 in, .11 in]
Connector System: Cable-to-Cable, Wire-to-Wire

Centerline (Pitch): 10.4 mm [.409 in]

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Plug
Connector System	Cable-to-Cable, Wire-to-Wire
Sealable	Yes
Primary Locking Feature	Integrated in Housing
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	4
Number of Rows	1, 2
Electrical Characteristics	
Operating Voltage	850 VDC
Body Features	
Cable Exit Angle	180°
Primary Product Color	Orange
Connector & Keying Code	В
Contact Features	

.63mm, 2.8mm

Contact Size



Contact Type	Receptacle
Mating Tab Width	.63 mm, 2.8 mm[.024 in][.11 in]
Mechanical Attachment	
Strain Relief	With
Terminal Position Assurance	No
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PA 66 GF
Centerline (Pitch)	10.4 mm[.409 in]
Dimensions	
Product Width	27.6 mm[1.09 in]
Product Length	32.9 mm[1.29 in]
Connector Height	68 mm[2.68 in]
Jsage Conditions	
Operating Temperature (Max)	140 °C[284 °F]
Operating Temperature Range	-40 – 140 °C[-40 – 284 °F]
Operation/Application	
Circuit Application	Power & Signal
ndustry Standards	
IP Rating	IP6K7, IP6K9K
UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Quantity	1
Packaging Method	Package
Other	
Serviceable	Yes

Product Compliance

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Dodecamethylcyclohexasiloxane (D6) (.26% in 35331746655) Decamethylcyclopentasiloxane (D5) (.26% in 35331746655) Octamethylcyclotetrasiloxane (D4) (.26% in 35331746655) Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts









4 Position Housing, Plug, Cable-to-Cable / Wire-to-Wire, 10.4 mm [.409 in] Centerline, Sealable, Orange, Wire & Cable, Power & Signal







YHV280-2pm-p-4mm-D



Customers Also Bought





















Documents

Product Drawings

HVA280-2phm,pass,4sqmm,Key B

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_YHV280-2PM-P-4MM-B_A.2d_dxf.zip

4 Position Housing, Plug, Cable-to-Cable / Wire-to-Wire, 10.4 mm [.409 in] Centerline, Sealable, Orange, Wire & Cable, Power & Signal



English

Customer View Model

ENG_CVM_CVM_YHV280-2PM-P-4MM-B_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_YHV280-2PM-P-4MM-B_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

HIVONEX CONNECTORS & CHARGING SOLUTIONS

English

HEMS Sample Kit YHV280-2pm-p-4mm-B

English

Product Specifications

Application Specification

English